

APPARATUS, SYSTEMS AND METHODS FOR
ELECTRONICALLY TEACHING PHONICS

5

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application No. 60/181,378 filed February 09, 2000, which is hereby incorporated by reference as if set forth in full herein.

10

FIELD OF THE INVENTION

The present invention relates generally to educational toys and specifically to educational toys for teaching phonics.

15

BACKGROUND OF THE INVENTION

20

The word "phonics" means a method of teaching beginners to read, spell and pronounce new words by learning the sounds of letters and letter groups. For each language, such as the English language, there have been numerous publications of sets of various rules by which the sounds of letters and letter groups can be described. However, the published sets of rules are complex, and in written form, are not well suited for teaching beginning speakers and readers of a language, such as very young children, to read, spell, or pronounce new words. Further, self-exploration of a new subject has been shown to be an effective way of learning. However, in the past, there has not been an effective way of providing beginners with a way of self-teaching phonics. Therefore, a way is needed to help beginners, such as very young children, learn to read, spell and pronounce new words.

25

30

SUMMARY OF THE INVENTION

35

The present invention provides apparatus, systems and methods for electronically teaching phonics. The exemplary embodiment provides a base unit with multiple receiving wells for

blocks. The outer surface of each face of each block expresses an alphabetic character. Each face of each alphabet block has
 5 a unique bit pattern expressed in a pattern of electrically conductive material that identifies the alphabetic character expressed on the outer surface of the opposing block face. Underneath the exposed surface of the floor of each block receiving well, is an electronic sensing device. The electronic
 10 sensing device uses capacitive coupling in accordance with a test bit pattern to identify the alphabetic character expressed by each block in each block receiving well. A computer device, such as a microprocessor, identifies phonetic relationships between the exposed letters and determines the phoneme for each exposed
 15 alphabetic character for each block in a block receiving well. The invention then audibly plays the phoneme representing each exposed alphabetic character according to a player's instructions.

The present invention provides apparatus, systems and
 20 methods for electronically teaching phonics that utilizes an individual's natural curiosity and willingness to explore to help beginning speakers and readers, such as very young children, develop their own sound heuristics. The exemplary embodiment of the invention described here is a toy that facilitates self-
 25 teaching of phonics in the English language for very young children. The exemplary toy is illustrative and is not a limitation of the invention. It should be understood by someone with ordinary skill in the art that the invention applies equally to more sophisticated models that provide more complex word and
 30 word combination building, and for languages other than English.

The present invention provides a base unit, also referred to as the "console". The base unit has a top, a bottom, a front orientation, and a back orientation. In the top of the base unit, there are five receiving block wells (also referred to as "block

stations") for lettered blocks. Four Mode buttons and a Play button are provided on the top of the base unit.

5 The four Mode buttons are used to select the mode of play: "Song", "Explore", "Spelling", or "Activity". The toy provides the child playing (the "player") with feedback, the type of feedback varying according to the mode in which the player has chosen to operate the toy. In Song mode, children can play with
10 blocks and music, and become familiar with the sound that each letter makes. In Explore mode, children can play with letters and the sounds they make by pressing the blocks in the block stations. In Spelling mode, children can practice spelling and sounding out words. In Activity mode, children can practice
15 finding letters in directed play.

Each block station displays a lighting feature such that when a block is placed into the well, the lighting feature, if on, is evident from the front orientation of the base unit.

As with the traditional alphabet blocks of yesterday, each
20 block for the present invention has six faces; each face of each block has a letter. For example, one block features the letters "A" on two faces, "B" on two faces, and "C" on the remaining two faces. Each letter is capitalized and underlined, the underline indicates the correct orientation of the letter for placement in
25 the well. On some block faces, instead of the letter, a picture for which the word describing the picture begins with the letter featured on that particular face of the block. For instance, a block face that features the letter "C" can display a picture of a Cat.

30 As opposed to traditional solid wooden blocks of yesterday, the blocks provided by the present invention provide an electronic sensing device pattern on the inside of each block face. The sensing pattern identifies the letter on the face opposite the face inside which the sensing pattern exists. The
35 floor of each block station provides a sensing device such that,

when a block is pressed into the block station, the sensing device in the floor of the block station identifies the letter, which is displayed on the top face of the block exposed in the block station.

The present invention provides a computer device, such as a microprocessor, which determines, among other things, the mode in which the toy is operating, the identity of each alphabetic character for all blocks resting in block stations, and relationships between the identified alphabetic characters.

The terms microprocessor and microcontroller are used interchangeably herein. The description of a microprocessor as the particular computer device by which the functions and processes described herein are performed is illustrative and not a limitation of the invention. Someone with ordinary skill in the art will understand that the invention applies equally, without departing from the spirit of the invention, to other computer devices, including for instance, a modem connection to a server computer over a global communications network such as the Internet.

The toy operates in multiple modes, depending upon the choice of the player. If the toy is operating in, for example, the Explore mode, the computer device applies phonics rules to deduce the sound of each letter according to its proximity to, and context with, other alphabetic characters ("letters") in the other block stations. Using voice circuitry, the computer device plays the sound for each letter, or if the letters spell a word, the computer device plays the sound of the word. As the computer device plays the sound for each letter, the computer devices uses electrical circuitry to light the lighting feature around the top surface of that block station.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a graphic representation depicting a front view
5 of an exemplary embodiment of the base unit of the present invention;

FIG. 2 is a graphic representation depicting a back view of
an exemplary embodiment of the base unit of the present invention;

10 FIG. 3a is a graphic representations depicting a cut-away side view of an exemplary block station;

FIGS. 3b-3c are graphic representations depicting a cut-away side view of an exemplary block in an exemplary block station;

15 FIGS. 4a-4e are graphic representations depicting exemplary configurations of blocks in an exemplary embodiment of the base unit of the invention;

FIG. 5 is a graphic representation depicting an exemplary configuration of blocks in an exemplary embodiment of the base unit of the invention;

20 FIG. 6 is graphic representation depicting a table of phonemes;

FIG. 7a is a graphic representation depicting an exemplary embodiment of a binary template;

25 FIGS. 7b-7c are graphic representations depicting the overlay of an exemplary embodiment of a binary template over block stations in the base unit of the invention;

FIGS. 8a-8d are a graphic representation of a portion of an exemplary embodiment of a dictionary of words and instructions;

30 FIG. 9 is graphic representation depicting the contents of an exemplary embodiment of the binary template overlaying block stations in an exemplary embodiment of the base unit of the invention;

FIG. 10 is a graphic representation depicting a six-faced block;

FIGS. 11a-11m are logic flow diagrams depicting the phonics rules logic for an exemplary embodiment of the invention;

5 FIG. 12 is a block diagram depicting one embodiment of the present invention;

FIG. 13 is a block diagram depicting the hardware architecture of one embodiment of the present invention;

10 FIG. 14 is a process diagram depicting generation of a phoneme sequence within one embodiment of the present invention; and

FIG. 15 is a process diagram depicting generation of a single phoneme within one embodiment of the present invention.

15 DETAILED DESCRIPTION OF THE INVENTION

FIG. 12 is a block diagram depicting one embodiment of the present invention. The invention comprises phonics engine 1200 for generation of phonemes in response to inputs received from a user interface 1202. A player uses the user interface to select a mode of play and to input an alphabetic sequence of alphabetic characters. The phonics engine responds by outputting a phoneme sequence consisting of one or more phonemes that is presented to the player through an audio transducer. A visual display information is also generated for presentation to the player.

25 The user interface is comprised of an input portion 1204 and an output portion 1210. The input portion is comprised of an alphabetic sequence sensor 1206 for sensing an alphabetic sequence and a mode sensor 1208 such as a multi-position switch for setting a playing mode. The output portion is comprised of an audio transducer 1212 for presentation of the phoneme sequence such as an audio speaker. The output portion further comprises a visual display 1214 for presentation of visual display information related to the phoneme sequence.

35

In operation, the player uses the alphabetic sequence sensor to arrange an alphabetic sequence such as a string of letters. The player sets the mode switch to invoke various play modes and the phonics engine responds by outputting a phoneme sequence through the audio transducer. The player also receives a visual display depicting the relationships between the phonemes in the phoneme sequence and the alphabetic sequence.

The phonics engine is comprised of a sequence parser 1216 operably coupled to the alphabetic sequence sensor and game logic 1218. The sequence parser receives the alphabetic sequence from the alphabetic sequence sensor and creates an internal representation of the alphabetic sequence for further processing by the phonics engine. The game logic is also operably coupled to the mode sensor. The game logic reads the mode sensor and accepts the alphabetic sequence and determines what kind of phoneme sequence is to be generated.

A phoneme generator 1228 is operably coupled to a word dictionary 1220 and a phoneme table 1222. The word dictionary contains a set of alphabetic sequences associated with phoneme keys and visual display generation instructions. The phoneme keys are indexes into the phoneme table where individual phonemes are stored. The phoneme generator searches the word dictionary to find a match for an input alphabetic sequence. If a match is found, the phoneme generator reads the phoneme keys and generates a phoneme sequence from the phoneme keys and phoneme table. If there is no match in the word dictionary for the alphabetic sequence, then the phoneme generator generates a phoneme sequence using a set of phonics rules. The phoneme sequence is output to the audio transducer for presentation to the player.

The phoneme generator also generates visual display information based on visual display generation instructions associated with the words stored in the word dictionary or based

on the phonics rules. The visual display information is presented to the player using the visual display.

5 FIG. 13 is a hardware architecture diagram for one embodiment of the present invention. The phonics engine 1200 is implemented using a microprocessor based controller with Input/Output (I/O) capabilities for both analog and digital signals. The controller is augmented with audio circuitry 1330,
10 visual display circuitry 1324, mode sensor circuitry 1318, and alphabetic sequence sensor circuitry 1314 for interfacing the phonics engine to components comprising the user interface 1202.

A CPU 1300 is operably coupled to Random Access Memory 1304 (RAM) and Read Only Memory (ROM) by system bus 1302. In
15 operation, the CPU uses programming instructions 1308 stored in the ROM to implement the logic of the phonics engine. The previously described word dictionary and phoneme table are stored on the ROM as well. The RAM is used by the CPU to store game playing difficulty levels between player interaction sessions.
20 The RAM is also used by the CPU for temporary data storage during generation of the previously described phoneme sequence and visual display information.

The CPU is operably coupled through the system bus and an Input/Output (I/O) bus 1310 to a Digital to Analog Converter 1328
25 (DAC) and a digital I/O interface 1312. The DAC is further operably coupled to audio circuitry 1330. The controller uses the DAC to create audio signals for digitally encoded phonemes stored in the phoneme table.

The digital I/O interface is operably coupled to visual
30 display circuitry 1324, mode sensor circuitry 1318, and alphabetic sequence sensor circuitry 1314.

The controller uses the digital I/O interface and visual display circuitry to send visual information signals to the user interface.

The controller uses the mode sensor circuitry to sense the state of mode setting switches in the user interface.

5 The controller uses the digital I/O interface and alphabetic sequence sensor circuitry to sense an alphabetic sequence entered by a player using the user interface.

10 The user interface 1202 comprises an audio speaker 1332 operably coupled to the audio circuitry for presentation of phonemes generated by the phonics engine to the player, a visual display composed of a plurality of lighting features 1326 operably coupled to the visual display circuitry for presentation of visual phoneme sequence information, a plurality of game mode setting switches 1322 operably coupled to the mode sensor circuitry for setting game modalities, and a plurality of stations 1316 operably coupled to the alphabetic sequence sensor circuitry for sensing individual elements of an alphabetic sequence composed by a player.

15 In operation, a player arranges physical objects representing the individual elements of an alphabetic sequence such that the physical objects are sensed by the plurality of stations. The player sets the game mode switches to select a particular mode of play. The phonics engine reads the mode switches and alphabetic sequence to create a phoneme sequence. 20 The phoneme sequence is presented to the player using the audio speaker. Additionally, a visual display is created by the phonics engine and presented to the player using the plurality of lighting features.

30 BASE UNIT

An exemplary embodiment of the present invention described herein, as depicted in FIG. 1, has a base unit 1, also referred to as a "console" 1. The base unit 1 has a top 2, a front orientation as depicted in FIG. 1, a back orientation as depicted in FIG. 2, and a bottom 3. As is also depicted in FIG. 1, in the 35

top 2 of the base unit 1, there are five receiving block wells 3-7 (also referred to as "block stations") for receiving lettered objects such as blocks or tiles. The presence of a lettered block or tile in a receiving well is used to determine one element of an alphabetic sequence. The the number of wells depicted in the exemplary embodiment is illustrative and not a limitation of the invention.

10 The base unit 1 further provides four Mode buttons 8-11 and a Play button 12 on the top 2 of the base unit 1. Each of the four Mode buttons 8-11 and the Play button 12 has a lighting feature 8a-12a respectively, such as an LED.

5 The base unit further provides a High/Low volume switch 13, a headphone jack 14, a Reset button 15, an AC adapter port 16, Cyber Cartridge receptacle 17 and is battery powered 18.

BLOCK STATION

20 Each block station 3-7 has a floor 3a-7a. The floor 3a-7a of each block station 3-7 has a surface which is described further below, underneath of each of which is provided an electronic sensing device 20 as depicted in FIGS. 3a-3c, each of which is provided with its own set of analog and digital electronics as described below and as disclosed in detail in copending U.S. Utility Patent Application attorney docket number 25 37539/FLC/N240, the disclosure of which is incorporated here by reference as if fully stated here for all purposes. In the exemplary embodiment depicted herein, a single computer device, e.g., a microprocessor, is shared by the multiple block stations 3-7.

30 As depicted in FIG. 3a, the surface of each block station floor 3a-7a in the exemplary embodiment features numerous tiny projections, e.g., 21a-21d, referred to here as "knuckles", that project upward from the block station floor 3a-7a. When the knuckles are at rest, the highest point of the upper surface of 35 each knuckle, e.g., 21a-1, is a certain distance 22 (referred to

herein as the "at-rest distance") from the surface of the floor, e.g., 3a, of the block station, e.g., 3. As depicted in FIG. 3b, when a player places a block, e.g., 23, in a block station, e.g., 3, the knuckles, e.g., 21a-21d support the block at the at-rest distance 22 from the block station floor, e.g., 3a. When the block merely rests on top of the knuckles as depicted in FIG. 3b, the microprocessor 30 for the sensing device 20 underneath the surface of the blocking station floor 3a senses the identification of the block and the at-rest distance 22 of the block from the sensing device 20 from the electrically conductive sensing pattern 26 inside the bottom surface of the block 23. From that information, the microprocessor 30 for the sensing device 20 deduces that the block is merely at rest. The toy responds to the at-rest position of the block 23 in the block station 3 according to the requirement of the mode in which the toy is being operated at the time.

The knuckles, e.g., 21a-21d, provide levitation of the block that rests on the knuckles. In alternative embodiments, other mechanisms are used to levitate a block at an at-rest distance from the block station floor surface, such as, for example, foam rubber.

As depicted in FIG. 3c, as opposed to an at-rest position in which the block 23 rests at an rest distance 22 from the sensing device 20, the player can press a block, e.g., 23, into a block station, e.g., 3. Pressing the block 23 into the block station 3, compresses the knuckles, e.g., 21a-21d, by a compression distance 24, so that the distance 25 between the sensing device 20 is smaller than the at-rest distance 22. The compression distance 24 is a variable that depends upon the amount of pressure with which the block 23 is pressed into the block station, e.g., 3. Accordingly, the distance 25 is a variable that can be calculated as the difference between the at-rest distance 22 and the compression distance 24. Alternatively,

the compression distance can be calculated as the difference between the at-rest distance 22 and the distance 25 as measured by the microprocessor 30. The microprocessor 30 detects the smaller distance 25 as compared to the at-rest distance 22 between the electrically conductive sensing pattern 26 inside the bottom surface of the block 23. From the distance calculated by the microprocessor 30, the microprocessor 30 deduces that the block is pressed into the block station, as opposed to being merely at rest. The toy will then respond to the pressed position of the block in the block station according to the requirement of the mode in which the toy is being operated at the time.

Each block station 3-7 has a lighting feature 3b-7b. The microprocessor 30 is connected to each of the lighting feature 3b-7b. The lighting feature is used as a feedback mechanism for the player.

20 BLOCKS

The exemplary Phonics toy embodiment provides a plurality of interchangeable blocks, an example of which is depicted in FIG. 3. In the exemplary embodiment of the Phonics toy described here, sixteen alphabet blocks are provided in four different colors. All letters displayed on the blocks are in upper case. The blocks are color-coded into four sections of the alphabet: A-F are blue; G-L are green; M-R are orange; S-Z are red.

Different block layouts are provided. One block layout provides three different letters, each letter appearing on the block on two different faces. Some letters are represented as pictures, for example, a picture of an apple is displayed instead of the letter A. A second block layout provides six (6) different letters. Each block face provides a visual cue, such as underlining, to indicate the bottom orientation of the letter

displayed on the face of the block that is visible from a top front orientation of the base unit 1.

5 In the exemplary embodiment of the Phonics toy depicted here, block layouts are as follows: 1) AABBBCC (blue); 2) DDEEFF (blue); 3) ABCDEF (blue) 4) ABCDEF (blue); 5) GGHHII (green); 6) JJKKLL (green); 7) GHIJKL (green); 8) GHIJKL (green); 9) MMNNOO (orange); 10) PPQQRR (orange); 11) MNOPQR (orange); 12) MNOPQR (orange); 13) SSTTUU (red); 14) UUVVWW (red); 15) XXYYZZ (red); 16) STUVWS (red). The block layouts described above are exemplary and not a limitation of the invention.

In one embodiment of the present invention, the blocks are replaced by a plurality of tiles. Each tile has a top surface and a bottom surface. The top surface of each tile has a letter displayed on it. The bottom surface of each tile mates with a block station.

MODES OF PLAY

20 When the toy is turned on, the toy plays a "Hello" sequence, and lights all lighting features 3b-7b for each block station 3-7 for a short time, such as .5 seconds. The toy then sequentially lights all lighting features 3b-7b for each block station 3-7 for a short time, such as .25 seconds, for a total start sequence time, of, for example, 1.25 seconds. The toy then begins to operate in a default mode, for example, the Song mode.

At any time while the toy is turned on, the player pressing one of the four Mode buttons will cause the lighting feature for that Mode button to light, the microprocessor announces that Mode, and the toy begins to operate in that Mode. If the base unit 1 of the toy is left inactive for 120 seconds, the microprocessor announces "Goodbye" and goes into a sleep Mode.

Song Mode

As mentioned above, Song Mode is the default Mode of operation for the toy. If the player turns on the base unit 1, or if the player presses the Song Mode button, the toy will announce the Song Mode and will play an introductory musical phrase that prompts the player to put a block in a block station to play the game. As an example, the toy plays "Put a block in. Press on the block . . .".

If the player does not respond within a certain time, for example 30 seconds, then the toy repeats the prompt. If the player does not respond within a certain time, for example 30 seconds, after the second prompt, the toy says "Goodbye" and goes into Sleep Mode.

The Song Mode operates in two submodes. In the first submode, the player must press a block into a blocking station to cause the toy to respond. In this first submode, once the player places a block, e.g., 23 as depicted in FIG. 3b, in a block station, e.g., 3 and presses the block 23 into the block station 3 as depicted in FIG. 3c, the toy plays a musical sequence that is based on a musical template that has been mapped to letter or picture depicted on the exposed block face. In an exemplary embodiment, a first musical template is mapped to block face letters A-F (green blocks); a second musical template is mapped to block face letters G-L (blue blocks); a third musical template is mapped to block face letters M-R (red blocks); and a fourth musical template is mapped to block face letters S-Z (orange blocks). The musical template mapping described above is provided for illustrative purposes and is not a limitation of the invention. In other embodiments, a separate musical template is mapped to each letter and to each picture.

A musical template is a set of predefined words and variables set to music. A default phoneme, a sound, for each letter is mapped to each letter. For example, the letter "C" can

be represented by several different phonemes, depending upon the context of the letter with respect to other letters. For purposes of the Song Mode, a default phoneme for the letter "C", such as the /k/ sound in the word "cat", is mapped to the letter "C".

The microprocessor 30 creates a musical sequence by merging the Song Mode phoneme mapped to the letter on the exposed face of the block with the musical template mapped to that letter. For example, a musical template for the letter "B" is: /*/ /*/ "That's a sound I like to say" /*/ /*/. The "/*/ " symbols represent a position for the playing of the phoneme for a letter. When a player presses a block with the letter "B" exposed on the top face into a well, e.g., 3, the toy identifies the letter as the letter "B" using the sensing technology described below, identifies the musical template mapped to that letter, identifies the phoneme mapped to that letter, merges the phoneme mapped to the letter "B" with the musical template mapped to the letter "B" and plays the following musical sequence: "/b/ /b/ That's a sound I like to say /b/ /b/".

In a second submode, the player presses the Play button 12, as depicted in FIG. 1. After the player has pressed the Play button 12, the toy successively plays the musical sequence according to the musical template and phoneme mapped to the letter depicted on the top surface face of each block that has been placed in a block station. After sequentially playing the musical sequences for each block, the toy plays a musical loop. If the player presses a button or a block, the toy stops playing the musical loop.

If the player presses on a block during any sequence or loop, the sequence or loop is interrupted and the toy plays the sound for the exposed block face.

If the player presses the Play button 12, such as is depicted in FIG. 1, during any sequence, the toy begins playing

the sequence again; if there is more than one block in the block stations 3-7, the toy plays the musical sequences, starting with the musical sequence for the block in the first block station beginning with block station 3; if there is only one block in a block station, then the toy plays the musical sequence for letter on the exposed face of that block.

If the player does not press a button or a block for a certain period of time, or for a certain number of times in which the musical loop is played, the toy announces "Goodbye" and goes into Sleep mode.

Explore Mode

In Explore Mode, the player can play with letters and combinations of letters to explore the sounds they make. To begin the Explore Mode, the player presses the Explore Mode button 9. The toy responds by lighting the Explore Mode button lighting feature 9a, announcing the Explore Mode, and loading, or otherwise accessing, phonics rules and the phonics engine, both of which are described in detail below.

If after thirty (30) seconds after entering the Explore Mode, the player has not put a block into a block station, the toy plays a prompt, e.g., "Put a block in and press it." If after thirty (30) seconds of inactivity, the player has put in a block, but has not pressed the Play button 12 or the block, the toy plays a prompt, e.g., "Press a block to get started." After an additional thirty (30) seconds of inactivity, the toy repeats the prompt that it last played. After 120 seconds of inactivity, the toy plays the word "Goodbye" and goes into Sleep mode.

In Explore Mode, the microprocessor 30 for the sensing device 20, as depicted, e.g., in FIG. 3a, determines, in a way that is described in detail as part of the Sensing Device section of this disclosure, the identity of each block that is placed in each well. If the player replaces one or more blocks in one or

more block stations with a different block, the microprocessor 30 for the sensing device 20 identifies each new block. Even though the microprocessor 30 identifies each block in each block station 3-7, in Explore Mode, the toy does not play sounds unless the player presses a block or presses the Play button 12.

If the player presses a block, the toy uses the phonics engine and phonics rules to determine the correct sound for the pressed letter. Reference herein to a pressed block, pressed block letter, or pressed letter refer to the letter that is displayed on the top exposed surface of a block in a block station. The toy, using the phonics engine and phonics rules, determines the sound of each pressed block letter in context with any other blocks that have been placed in any other block stations 3-7.

If, on the other hand, the pressed block is the only block in a block station, or if the pressed block letter is not affected by any other placed block, the toy recognizes the context, plays the correct sound of the sound for the pressed block letter, and lights the lighting feature associated with the block station in which the pressed block letter rests. This situation is illustrated in an example as depicted in FIG. 4a. Note that in the FIGURES, diagonal marking of a light feature, e.g., 3b-7b, 8a-12a, indicates that the light feature is lighted.

As depicted in FIG. 4a, there are three blocks: a "C" block 41, an "A" block 42, and a "T" block 43 in block stations 3-5 respectively; block stations 6-7 are empty. The microprocessor 30 (not shown in FIG. 4a) for sensing device 20 (not shown in FIG. 4a) determines the identity of each of the three blocks. As is depicted in FIG. 4a, with the toy in Explore mode 9, the Explore mode light feature 9a is lighted. The player 40 presses the "C" block 41 into block station 3. The microprocessor 30, using the phonics engine and phonics rules, determines that, and plays the sound /k/ for, the letter "C" as in the word "Cat", and

lights the light feature 3b for the block station in which the pressed letter is pressed, in this case, 3.

5 If the blocks 41, 42 and 43 are in block stations 3-5 as depicted in FIG. 4a, and if the player presses the Play button 12, the Play button light feature 12a is lighted and the microprocessor forms a "word" the three block letters ("C", "A", and "T") attempts to look for the "word" in a dictionary
10 table/database. The dictionary table/database is described in the phonics engine section of this disclosure. The microprocessor finds the word "Cat" in the dictionary/database, the toy plays the word "Cat" and lights up all of the light features 3b-5b for the block stations 3-5 in which the blocks 41, 42 and 43 rest.

15 If, when the player presses the Play button 12 while the toy is in Explore mode, the microprocessor 30 does not find the word in the dictionary, the toy plays the sound (phoneme) for each letter or letter group separately and consecutively, such as when a human sounds out a word. As it plays each phoneme, the toy
20 lights the light feature for the block station(s) for which it is playing a phoneme, including adjacent letters that form what is known as a "digraph" (a digraph is a group of two successive letters that have a single sound, such as the "CH" in the word "chart").

25 If the sound of the pressed block letter is affected by any other placed blocks, the toy recognizes the context, plays the correct sound for the pressed block letter, and lights the lighting feature associated with the block station in which the pressed block letter rests and the lighting feature(s) associated
30 with the block station(s) in which a block letter has been placed that affects the pressed block letter. This situation is illustrated in FIGS. 4b-4e.

In FIG. 4b, there are four blocks: a "C" block 41, an "H" block 44, an "A" block 42, and a "T" block 43 in block stations
35 3-6 respectively; block station 7 is empty. The microprocessor

30 (not shown in FIG. 4b) for sensing device 20 (not shown in FIG. 4b) determines the identity of each of the four blocks. As
 5 is depicted in FIG. 4b, with the toy in Explore mode 9, the Explore mode light feature 9a is lighted. The player 40 presses the "C" block 41 into block station 3. The microprocessor 30, using the phonics engine and phonics rules, determines that, and plays the sound /ch/ for, the letter "C" as in the word "Chat",
 10 and lights the light feature 3b for the block station in which the pressed letter is pressed, in this case, 3, and lights the light feature 4b for the block station 4 in which the "H" block 44 rests.

As depicted in FIG. 4c, the player 40 then presses the "A"
 15 block 42 in block station 5. The system then plays the /a/ sound as in the word "chat" and lights the light feature 5b for the block station 5 in which the "A" block 42 is pressed.

The player then replaces the "T" block 43 with an "R" block 45 in block station 6, and places the "T" block 43 in block
 20 station 7 as depicted in FIG. 4d. The player 40 then presses the "A" block 42 in block station 5. The microprocessor 30 (not shown in FIG. 4d) for sensing device 20 (not shown in FIG. 4d) determines the identity of each of the five blocks ("C", "H", "A", "R", and "T"). As is depicted in FIG. 4d, with the toy in
 25 Explore mode 9, the Explore mode light feature 9a is lighted. The microprocessor 30, using the phonics engine and phonics rules, determines that, and plays the sound /ă/ for the letter "A" as in the word "Chart", and lights the light feature 5b for the block station in which the pressed letter is pressed, in this
 30 case, 5, and lights the light feature 6b for the block station 6 in which the "R" block 45 rests.

Next, as depicted in FIG. 4e, the player replaces the "R" block 45 with an "S" block 46 in block station 6, and replaces the "T" block 43 in block station 7 with an "E" block 47. The
 35 player 40 then presses the "A" block 42 in block station 5. The

microprocessor 30 (not shown in FIG. 4e) for sensing device 20 (not shown in FIG. 4e) determines the identity of each of the five blocks ("C", "H", "A", "S", and "E"). As is depicted in FIG. 4e, with the toy in Explore mode 9, the Explore mode light feature 9a is lighted. The microprocessor 30, using the phonics engine and phonics rules, determines that, and plays, the sound /ā/ for the letter "A" as in the word "Chase", and lights the light feature 5b for the block station in which the pressed letter is pressed, in this case, 5, and lights the light feature 7b for the block station 7 in which the "E" block 47 rests.

Spelling Mode

15 The player enters the Spelling Mode by pressing the Spelling Mode button 10. When pressed, the Spelling Mode button light feature 10a lights and the toy announces "Spelling". The toy's microprocessor 30 loads the player's skill level, the word list for that level, and the phonics engine and phonics rules. If the 20 player has not previously played the Spelling Mode, the toy's microprocessor 30 loads a beginner's skill level as the player's skill level. If the player has previously played the Spelling Mode, the toy's microprocessor 30 loads a previously determined skill level as the player's skill level.

25 The microprocessor picks words pseudo-randomly from the word list for the player's skill level. For each word selected, the toy selects one of various prompt templates, including, e.g.: "Spell", "Let's spell", "Please spell", and "Now spell". The microprocessor merges the selected word, e.g., "Bat" with the 30 selected prompt template to form a prompt for the selected word. The toy then prompts the player to, e.g., "Spell Bat".

If the toy remains inactive, such as when the player does not place any blocks in any block stations, or presses the Play button 12 without having placed any blocks in any block stations, 35 then the toy prompts the player to "Put a block in." and repeats

the prompt, e.g., "Spell Bat". After 120 seconds of inactivity, the toy plays the word "Goodbye" and goes into Sleep Mode.

5 If the player places the incorrect blocks in the block stations (for instance, "C", "A" and "T" when the word to spell was "Bat") and presses the Play button 12, the microprocessor 30 determines that the word spelled is incorrect. Then the microprocessor 30 determines, according to the phonics engine and
10 the phonics rules, the phonemes for the letters played, and merges the phonemes with a template that plays "Oops, you spelled". The toy then plays the merged message that says, e.g., "Oops, you spelled /c/ /a/ /t/." The toy then merges the phonemes for the correct spelling of the word with the spell
15 prompt, and plays the merged spell prompt, e.g., "Spell Bat, /b/ /a/ /t/".

If the player is unable after three tries, each try being measured by the player pressing the Play button 12, then the toy ends the round by announcing "Let's spell a different word." The
20 toy then begins a new round by announcing "Let's try a different word. Spell" e.g., "Boy".

In the Spelling Mode, if the player puts a block in a block station and presses the block, the toy plays the phoneme for the letter. If other blocks are in other block stations, the phoneme
25 is determined in context with the other letters. If the pressed block letter is part of a digraph, the toy plays the phoneme for the digraph and lights the light features for both the pressed block and the other block station in which the remaining component of the digraph rests. If the pressed block letter is
30 not part of a digraph, then the toy lights the light feature for the block station in which the block letter is pressed and plays the phoneme for the individual pressed block letter, in context with the other block letters in any other block stations.

If the player has correctly spelled the prompted word and
35 presses the Play button 12, the toy randomly selects and plays

a congratulatory reinforcement, such as: "Great", "Super", "That's right!", "Yes!" in combination with a celebratory sound effect. The celebratory sound effect is created by the toy randomly selects and plays separate "wav" files, that typically each last between .1 and .5 seconds. With increases in the player's skill level, the number and length of sound effects increases.

10 If the player correctly spells seven (7) consecutive words from the player's current skill level, then the toy plays "You're a great speller!" and increments the player's skill level by one (1). The microprocessor 30 pulls words from the player's current skill level and all previous skill levels. A larger percentage of words are pulled from the current skill level. For example, 15 for a player at level four, 80% of the words will be pulled from the level four list, 15% from level 3, 4% from level 2, and 1% from level 1.

20 If the player misspells fifteen (15) words from the player's current skill level, the player's skill level is decremented by one level and the count of misspelled words is reset to zero.

Activity Mode

25 If the player presses the Activity Mode button 11, the toy announces "Activity". The toy's microprocessor 30 then loads the player's skill level, and the phonics engine and phonics rules. If the player has not previously played the Activity Mode, the toy's microprocessor 30 loads a beginner's skill level as the player's skill level. If the player has previously played the 30 Activity Mode, the toy's microprocessor 30 loads a previously determined skill level as the player's skill level.

35 The toy then plays "Put a block in and press the play button." If the player does not respond, or if the player presses the Play button 12 but places no blocks in the console, then after a period of thirty (30) seconds of inactivity, the toy

repeats the prompt "Put a block in and press the Play button."
Once again, if the player does not respond, or if the player
5 presses the Play button 12 but places no blocks in the console,
then after a second period of thirty (30) seconds of inactivity,
the toy repeats the prompt "Put a block in and press the Play
button." After 120 seconds of inactivity, the toy announces
"Goodbye" and goes into Sleep Mode.

10 When the player presses the Play button 12 and there is at
least one block in one of the block stations, the microprocessor
30 randomly selects the letter of one of the blocks in the block
stations and prompts the player to press that letter, by
announcing "Press the letter that makes the sound" and then plays
15 the phoneme of the letter that has been selected. For example,
as depicted in FIG. 5, in Activity Mode (the Activity Mode button
11 light feature 11a is lighted as depicted by the diagonal
marking), the player has placed the "R" block 45 in block station
3, the "E" block 47 in block station 4, and the "D" block 48 in
20 block station 5, and has pressed the Play button 12 (as depicted
by the diagonal marking lighting the Play button light feature
12a). The microprocessor 30 using the sensing device 20
identifies each of the blocks as "R", "E" and "D" respectively.
The microprocessor 30 uses the phonics engine and phonics rules
25 to determine the phoneme of each of the letters in context to the
other letters present in the block stations. The microprocessor
30 then randomly selects one of the letters, which in the example
is the letter "E", and instructs the player to "Press the letter
that makes the sound /e/".

30 If the player skill level is level one, then the
microprocessor 30 lights the light feature of the block station
in which the selected letter rests as an additional prompt for
the player.

If the player presses the incorrect letter, for example, the
35 "R" block 45, the microprocessor 30 lights the light feature of

the block station, in the example, block station light feature 3b, in which the player pressed the block and plays "You pressed" and plays the phoneme of the letter pressed /r/. The microprocessor then repeats the prompt, as in our example, to "Press the letter that makes the sound /e/". If the player presses an incorrect letter three times, then the toy prompts the player to press a different letter.

If the player presses the correct letter, which in the example is the "E" block 47, the microprocessor 30 lights the light feature of the block station, which in the example is the light feature 4b, in which the block was correctly pressed and plays a congratulatory sequence that includes a statement, such as: "Great!", "Super!", "That's right!", or "Yes". The congratulatory sequence also includes celebratory sound effects. With each successive correct answer, the microprocessor 30 creates a shorter sound effect to increase the speed of the game.

If after pressing correct letters forty (40) times, the player has not moved any of the blocks, the toy prompts the player to rearrange the blocks by playing "Let's mix up the blocks and play some more." If the player does not place any blocks in the base unit 1, after thirty (30) seconds of inactivity, the toy prompts the player to press "Put a block in and press the Play button."

If the player presses the Play button 12 after the toy plays a phoneme, the toy repeats the phoneme. In the first skill level, the toy lights the light feature of the block station in which rests the block with the letter for which the phoneme was repeated.

After the player has pressed seven (7) correct letters in a row, the microprocessor 30 increments the skill level by one level. After the player has pressed three (3) incorrect letters

in a row, the microprocessor 30 decrements the skill level by one level.

As the skill level advances, the prompts are reduced to playing the phonemes only, and the congratulatory sequences are shortened, eliminating the verbal phrases, and shortening the celebratory sound effects in order to accelerate the speed with which the player is expected to play the game.

PHONICS ENGINE AND PHONICS RULES

Table of Sounds

Forty-eight (48) sounds, or phonemes, of English are provided in an exemplary embodiment of a phoneme table, a visual representation of which is depicted in FIG. 6. The phoneme table provides a number, e.g., 101a for each phoneme. The number is used as a key into the table. Associated with each number, e.g., 101a, is a phoneme, e.g., 101b. In FIG. 6, phonemes are represented by a standard phonetic visual representation, such as the case for the first entry in the table, "/b/" for the "b" sound in the word "bat". The phoneme table, stored in the memory of the toy, does not contain the word "bat". Rather, the table only provides the number key, e.g. 101a, and a digital representation of the sound, e.g., 101b.

Binary Template

One aspect of the interface between the five block stations 3-7 and the phonics engine software executed by the microprocessor 30 is a five digit binary template 200 as depicted in FIG. 7a. FIG. 7a is a graphic representation conceptually depicting the five digit binary template 200. Someone with ordinary skill in the art will understand that the "template" 200 which is conceptually represented graphically in FIG. 7a is a five digit data field in memory. As depicted in FIG. 7a, the

left-most digit 201 of the template 200 represents the value 1; the next digit 202 represents the value 2; the next digit 203 represents the value 4; the next digit 204 represents the value 8; and the right-most digit 205 represents the value 16.

The microprocessor 30 determines the first (left-most, beginning with block station 30) block station in which a block rests. The microprocessor 30 then overlays, the left-most block station in which a block rests with the first (left-most) digit 201 of the binary template 200. In the manner described below, the microprocessor 30 creates accessible relationships, such as in a cross-reference table, between: the left-most block station in which a block rests and the first (left-most) digit 201 of the binary template 200; and between each subsequent block station in which a block rests and the respective digit of the binary template 200. Examples are provided in FIGS. 7b and 7c and described below to illustrate the application of the binary template 200.

In FIG. 7b, an "R" block 45 rests in the left-most block station 3; an "E" block 47 rests in the next block station 4; and an "D" block 48 rests in the next block station 5. The microprocessor 30 identifies each block letter using the sensing device and identifies the block station in which each block letter rests as described in the preceding sentence. The microprocessor 30 then overlays the binary template 200 so that the left-most digit 201 of the binary template 200 is associated with block station 3, which is the first block station in which a block, the "R" block 45, rests. Having identified block station 3 as the first block over which to overlay the binary template 200, the microprocessor 30 overlays: the second binary digit 202 over block station 4; the third binary digit 203 over block station 5; the fourth binary digit 204 over block station 6; and the fifth binary digit 205 over block station 7. The

microprocessor 30 thus creates a three-tiered relationship for the example depicted in FIG. 7b as follows:

<u>BLOCK STATION</u>	<u>LETTER</u>	<u>BINARY DIGIT</u>
3	R	201
4	E	202
5	D	203
6	blank	204
7	blank	205

In FIG. 7c, the "R" block 45 rests in the middle block station 5; the "E" block 47 rests in the next block station 6; and the "D" block 48 rests in the right-most block station 7. The microprocessor 30 identifies each block letter using the sensing device and identifies the block station in which each block letter rests as described in the preceding sentence. The microprocessor 30 then overlays the binary template 200 so that the left-most digit 201 of the binary template 200 is associated with block station 5, which is the first block station in which a block, the "R" block 47, rests. Having identified block station 5 as the first block over which to overlay the binary template 200, the microprocessor 30 then overlays: the second binary digit 202 over block station 6; and the third binary digit 203 over block station 7; the fourth binary digit 204 and the fifth binary digit 205 of the binary template 200 are not associated with any block station in this example. The microprocessor 30 thus creates a three-tiered relationship for the example depicted in FIG. 7c as follows:

<u>BLOCK STATION</u>	<u>LETTER</u>	<u>BINARY DIGIT</u>
3	blank	not applicable
4	blank	not applicable
5	R	201

6	E	202
7	D	203

5

The microprocessor 30 then uses the three-tiered accessible relationships described above between block stations in which lettered blocks rest 3-7, the corresponding letters, and the respective digits of the binary template 200 to manage the phonic interpretation of the phonemes of the letters present in the block stations 3-7, and the associated educational feedback to the player, such as the lighting of the appropriate block station light feature 3b-7b.

15

Dictionary of Words

20

The microprocessor 30 uses the identified letters present in the identified block stations and the above-described three-tier accessible relationships with the binary digits of the binary template 200 to build an alphabetic sequence from which a word search key is created to search for a word in a word dictionary. A portion of an exemplary embodiment of a word dictionary is depicted in FIGS. 8a-8d.

25

30

As depicted in, e.g. FIG. 8a, and as explained in more detail below, the dictionary provides coded instructions, e.g. 303-309, for each single-, two-, three-, and four-letter word contained in the dictionary, e.g. 300. Each word entry, e.g., the entry for the word "ace" 300, in the dictionary contains, among other things, a number identifier key 301, which in the case of the entry for the word "ace" is 29; an alphabetic key 302 representing the letters of the word; a text representation of the word 303; a numeric key into the phoneme table for each letter in the word, e.g., 304-306; and instructions 307-309 for generating a visual display such as lighting the lighting features associated with the block stations in which the block

35

letters forming the letters of the alphabetic sequence entry rest.

5 The example depicted in FIG. 9 is illustrative of an application of the dictionary. The microprocessor 30, using the sensing device 20, identifies that, as depicted in FIG. 9, the player has placed an "A" block 42 in block station 4; a "C" block 40 in block station 6; and an "E" block 47 in block station 7.

10 The microprocessor 30, as depicted in FIG. 9, then associates: the first digit 201 of the binary template 200 with the letter "A" 42 in block station 5; the second digit 202 of the binary template 200 with the letter "C" 40 in block station 6; and the third digit 203 of the binary template 200 with the letter "E" 47 in block station 7 creating the alphabetic sequence "ACE".

15 The microprocessor 30 looks up the alphabetic sequence "ACE" in the dictionary and locates entry 300 number 29, 301, for the word "ace" 302, 303.

20 The first phoneme instruction 304 instructs the microprocessor 30 that if the player presses the "A" block 42 in block station 5 to play the phoneme /ā/ 126b for the phoneme entry 126a (entry number 26 in the phoneme table) depicted in FIG. 6. The first feedback instruction 307 instructs the microprocessor 30 that if the player presses the "A" block 42 in

25 block station 5 to light the lighting features associated with the binary digits of the binary template 200 for which a value of 1 is provided. Specifically, the first feedback instruction 307 contains the value of "05" which is the decimal equivalent of the binary representation 00101; the values in the binary

30 template 200 are saved from left to right, so that the binary representation 00101 is saved in the first digit 201a as a "1"; in the second digit 202a as a "0"; and in the third digit 203a as a "1".

35 These instructions mean that if the player presses the letter "A" in block station 5 to light the lighting feature 5b

associated with block station 5 associated with the first binary digit 201a and to light the lighting feature 7b associated with block station 7 associated with the letter "E" which is in turn associated with the third binary digit 203a. The instructions are coded for the word "ace" in this way to demonstrate to the player that the letter "e" in the word "ace" effects the sound of the letter "a" in the word "ace".

10 The instructions described above also mean that if the player presses the letter "E" in block station 7 to be silent (because the "e" in the word "ace" has no sound) and to light the lighting feature 5b associated with block station 5 associated with the first binary digit 201a and to light the lighting feature 7b associated with block station 7 associated with the letter "E" which is in turn associated with the third binary digit 203a.

15 As described above, the toy teaches the player phonics even in the absence of a recognizable word. Therefore, if the microprocessor 30 does not find the alphabetic sequence as a word in the dictionary, the toy still sounds the phonemes of the alphabetic sequence as a phoneme sequence and lights the lighting features of the block stations to indicate to the player the interplay effects between the elements of the alphabetic sequence.

20 FIG. 14 is a process diagram depicting generation of a phoneme sequence within one embodiment of the present invention. The phonics engine determines an alphabetic sequence 1402 from blocks or tiles positioned in stations by a player and parsed 1400 into an internal representation of the alphabetic sequence as previously described. The phonics engine searches for the alphabetic sequence in a word dictionary 1401. If a match is found 1408 for a word and the alphabetic sequence, the phonics engine uses the coded instructions associated with the word in the word dictionary and the phoneme table 1410 to build 1416 a

25 30 35

phoneme sequence and visual display. The phoneme sequence and
visual display 1420 is outputted 1418 for presentation to the
5 player.

If no match is found 1408 for a word and the alphabetic
sequence, the phonics engine uses phonics rules 1414 and a
phoneme table 1412 to build a phoneme sequence and visual
display. The phoneme sequence and visual display 1420 is
10 outputted 1418 for presentation to the player.

FIG. 15 is a process diagram depicting generation of a
single phoneme within one embodiment of the present invention.
The phonics engine determines an alphabetic sequence 1502 from
blocks or tiles positioned in stations by a player and parsed
15 1500 into an internal representation of the alphabetic sequence
as previously described. The phonics engine next determines 1503
which block or tile was selected so that a single phoneme can be
generated for the selected block or tile. The phonics engine
searches for the alphabetic sequence in a word dictionary 1501.
20 If a match is found 1508 for a word and the alphabetic sequence,
the phonics engine uses the coded instructions associated with
the word in the word dictionary and the phoneme table 1510 to
determine 1516 a phoneme and visual display. The phoneme and
visual display 1520 is outputted 1518 for presentation to the
25 player.

If no match is found 1508 for a word and the alphabetic
sequence, the phonics engine uses phonics rules 1514 and a
phoneme table 1512 to build a phoneme and visual display. The
phoneme and visual display 1520 is outputted 1518 for
30 presentation to the player.

In one embodiment, if the alphabetic sequence is not found
in the word dictionary, the alphabetic sequence, the phoneme
sequence and the visual display generated using the phonics rules
are stored in the word dictionary as a virtual word for later
35 use.

Letter Dictionary

5 If only a single block letter is placed in a block station,
 then the "dictionary" definition of the sound for that letter is
 played. Each dictionary definition identifies whether or not the
 letter is a vowel and the normal sound of the letter, using the
 phoneme table key. Appendix D hereto contains exemplary code
 that sets up a Letter Dictionary and establishes the dictionary
 10 definition for each letter.

Phonics Rules

15 If the microprocessor 30 does not find a word matching the
 alphabetic sequence in the dictionary, then the microprocessor
 30 analyzes the alphabetic sequence according to a set of phonics
 rules in order to develop the phoneme to play when the player
 presses a particular letter and to develop the lighting
 configuration appropriate for the letters in the block station.

FIGS. 11a-11m are logic flow diagrams depicting the phonics
 rules logic flow for an exemplary embodiment of the invention.
 20 As depicted in FIGS. 11a-11m, in order to begin the phonics rules
 analysis, the microprocessor 30 builds a virtual word 400
 dictionary entry that provides phoneme sequence and lighting
 feature lighting instructions in the same format as a dictionary
 word entry. Following is exemplary code that builds a set of
 25 null virtual words, one virtual word for each possible word
 length (2 through 5 letters).

```

/vword2 [ "empty" [ "0" "0" ] [ "00" "00" ] false ] def
/vword3 [ "empty" [ "0" "0" "0" ] [ "00" "00" "00" ]
30   false ] def
/vword4 [ "empty" [ "0" "0" "0" "0" ] [ "00" "00" "00"
   "00" ] false ] def
/vword5 [ "empty" [ "0" "0" "0" "0" "0" ] [ "00" "00"
   "00" "00" "00" ] false ] def

```

35

1 42624/FLC/N240

```
/vwordtable [ nil nil vword2 vword3 vword4 vword5 ] def
```

5 Once the microprocessor 30 builds null virtual words for each possible length of a word according to the exemplary embodiment of the invention, the microprocessor 30 executes the various tests for various possible relationships between the letters.

10 The exemplary code used to program the exemplary embodiment of the invention and used herein to illustrate the various features of the present invention is an original programming language.

15 Following is exemplary code that executes the various tests to build the virtual word dictionary entry. (the ellipses is used in the following example for brevity to indicate that all passes vpass1 through vpass50, and vpass100 through vpass101 are executed):

```
20 /virtualword {  
    /wlen word length def  
    wlen 0 gt {  
        /workingvword vwordtable wlen get def  
        50 dict begin  
        "pass1" debugprint  
25         vpass1  
        . . .  
        "pass101" debugprint  
        vpass101  
        end  
30         gc  
        workingvword  
    } if  
} def
```

35

Someone with ordinary skill in the art will understand that the particular order of the execution of the phonics rules tests, as illustrated by the above code and as described below, is exemplary and is not a limitation of the invention. Other sequences of performing the tests can be devised without departing from the spirit of the invention.

In an exemplary embodiment, the microprocessor 30 applies over fifty (50) different tests ("passes") to the letters in the block stations to determine the most appropriate phoneme and lighting feedback configuration for each letter. Appendix A hereto contains a description of the more than fifty (50) rules with which each letter is tested in an exemplary embodiment of the invention if the letters were not found to be a word in the dictionary. Appendix B hereto contains an exemplary embodiment of the code for each pass. For example, "Pass 25" in Appendix A is supported by the exemplary code under the title "vpass25" in Appendix B.

In the first pass of the exemplary embodiment, "vpass1" assigns the "normal" sound for each letter in the virtual word to each position in the phoneme instruction subtable of the virtual word table 400 as depicted in FIG. 11a. In Pass 1, the microprocessor 30 shifts through each letter of the virtual word to assign each letter its normal sound; and to light the block station for that letter 401. The following exemplary code for "vpass1" is illustrative:

```
/vpass1 {
  0 1 wlen {
    /x exch def
    workingvword 1 get          // array
    x                          // array int
    Alphabet word x get get     // array int dict
```

1 42624/FLC/N240

```
                                /snorm get                                // array int
string
5                                put
                                workingvword 2 get
                                x 1 x bitshift put
                                } for
                                } def
```

10

If a player presses a letter block, the microprocessor 30 will light the lighting feature for the block station in which the letter block has been pressed; as described below, if the pressed letter is determined to belong to a phonetic relationship with other letters resting in other block stations, the phonics rules described below set lighting configurations to light the lighting features for the blocks in which the other letters belonging to the phonetic relationship rest.

15
20
25
30
35

Therefore, if a letter "X", for example, does not belong to a phonetic relationship with any other letters in the other block stations, then if the player presses that letter "X", the lighting feature for the block station in which the letter "X" was pressed will be lighted; if the player presses any other letter, then the lighting feature for the block station in which the letter "X" rests will not light.

On the other hand, if the letter "X" belongs to a phonetic relationship with other letters in other block stations, if the player presses the letter "X", then the lighting features for the block station in which the letter "X" was pressed and for the block stations in which the other letters in the phonetic relationship rest will light; if the player presses one of the other letters that belong to the phonetic relationship to which the letter "X" belongs, the lighting feature for block station in which the pressed letter was pressed, as well as the block stations for the other letters, including the letter "X", in the

phonetic relationship rest, will be lighted. References to lighting a block station in the description of the logic flow depicted in FIGS. 11a-11m means setting the lighting instruction to light the lighting feature for the block station referenced.

Thereafter, each "vpass" code section analyzes the possible phonetic relationships between the letters in the virtual word, and assigns the appropriate phoneme to letters in identified phonetic relationships, using the phoneme item number from the phoneme table as depicted in FIG. 6, to each letter in the letter combination being examined. Each "vpass" code section also assigns the appropriate lighting feedback configuration for the lighting features associated with the block stations in which letters identified as part of a phonetic relationship rest.

In Pass 2 of the exemplary embodiment, the microprocessor 30 finds each consonant in the virtual word 402a. If the letter preceding a consonant is also a consonant, and if the two consonants are the same consonant, the microprocessor 30 is programmed to: assign first consonant the silence phoneme #0; allow second consonant to default to its normal sound; and light block stations for both consonants 402b.

In Pass 3 of the exemplary embodiment, if the virtual word has the letter 'h', and if the letter 'c' immediately precedes the letter 'h', the microprocessor 30 is programmed to: assign the /ch/ phoneme #19 to both the 'c' and the 'h'; and light block stations for both 'c' and 'h' 403.

The following exemplary code for "vpass3" analyzes the letters in the virtual word for the "ch" combination of letters and is illustrative of the assignment of phoneme and lighting configuration feedback instructions:

```
// ch
/vpass3 {
    /prev '.' def
```

```

0 1  wlen {
      /x exch def
5      word x get 'h' eq prev 'c' eq and {
          x x 1 sub light2gether
          "19" x soundlikethis
          "19" x 1 sub soundlikethis
      } if
10     /prev word x get def
      } for
    } def

```

15 In the above depicted exemplary "vpass3" code, the microprocessor 30 looks for an 'h'. When an 'h' is found, the letter preceding the 'h' is examined to determine whether that letter preceding the 'h' is a 'c'. If so, the microprocessor 30 assigns the "19" sound 119a as depicted in FIG. 6, which is the /ch/ sound 119b in the word "cheese" as depicted in FIG. 6. Further, the
20 microprocessor 30 assigns the lighting instruction to each block in which the letters 'c' and 'h' rest.

The above exemplary code works from right to left, first looking for the letter 'h', at any position in the virtual word, and then looking in front of the 'h' for the letter 'c'. Other
25 "vpasses" work from left to right.

In Pass 4 of the exemplary embodiment, if the virtual word has the letter 't', and if the letter immediately preceding the letter 't' is the letter 'h', and if the letter immediately preceding the letter 'h' is the letter g, then the microprocessor
30 30 is programmed to: assign the silence phoneme #0 to both the 'g' and 'h' block stations; allow the 't' letter to default to its normal sound; and light all three block stations for 'g', 'h', and 't' 404.

In Pass 5 of the exemplary embodiment, if the virtual word
35 has the letter 'g', and if the letter immediately following the

1 42624/FLC/N240

'g', is 'e' or 'i', then the microprocessor 30 is programmed to:
assign the letter 'g' the /j/ phoneme #6; light both block
5 stations for 'g', and for the 'e' or 'i' 405.

In Pass 6 of the exemplary embodiment, if the virtual word
has the letter 'c', and if the letter immediately following the
letter 'c', is 'e' or 'i', then the microprocessor 30 is
programmed to: assign the letter 'c' the /s/ phoneme #13; and
10 light both block stations for 'g', and for the 'e' or 'i' 406.

The following exemplary code for "vpass6" illustrates a left
to right analysis approach, looking for a soft 'c', which is the
case whenever the letter 'c' is followed by either the letter 'i'
or 'e'.

15 // soft 'c'
/vpass6 {
0 1 when 1 sub {
/x exch def
20 word x get 'c' eq {
word x 1 add get 'i' eq
word x 1 add get 'e' eq
or {
x x 1 add lightthistoo
25 "13" x soundlikethis
} if
} if
} for
} def

30

In Pass 7 of the exemplary embodiment, if 'k' is the last
letter of the virtual word, and if the letter 'k' is immediately
preceded by the letter 'c', then the microprocessor 30 is
programmed to: assign the /k/ phoneme #7 to both the 'k' and the
35 'c'; and light both the 'k' and the 'c' block stations 407.

Some phonetic relationship tests, such as the above-described 'ck' test, look for certain letters and/or letter combinations at the ending of a word. The following exemplary code, "vpass7", illustrates an end of a word analysis, checking for the 'ck' combination, such as in the word 'check'.

```

10 // 'ck' at the end
/vpass7 {
    word when 2 sub get 'c' eq {
        word when 1 sub get 'k' eq {
            when 2 sub when 1 sub light2gether
            "7" when 2 sub soundlikethis
15      "7" when 1 sub soundlikethis
        } if
    } if
} def

```

20 In Pass 8 of the exemplary embodiment, if 'k' is the first letter of the virtual word, and if the letter 'k' is followed by the letter 'n', then the microprocessor 30 is programmed to: assign the letter 'k' the silence phoneme #0; and light both the 'k' and the 'n' block stations 408.

25 In Pass 9 of the exemplary embodiment, if 'w' is the first letter of the virtual word, and if the letter 'r' immediately follows the letter 'w', then the microprocessor 30 is programmed to: assign the 'w' the silence phoneme #0; and light both the 'w' and the 'r' block stations 409.

30 Some phonetic relationship tests such as the above-described 'wr' pass, look for certain letters and/or letter combinations at the beginning of a word. The following exemplary code, "vpass9", illustrates a beginning of a word analysis, checking for the 'wr' combination, such as in the word 'write'.

1 42624/FLC/N240

```

    // 'wr' at the beginning
/vpass9 {
5    word 0 get 'w' eq {
        word 1 get 'r' eq {
            0 1 lightthistoo
            "0" 0 soundlikethis
        } if
10    } if
    } def
```

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
22

the block stations for the letter 'r', and 'e', and for the letters 'a' or 'o' 412.

5 In Pass 13 of the exemplary embodiment, if the virtual word ends in the letter 'y', and: if the virtual word has no vowels, then assign the letter 'y' the /ī/ phoneme #28; else if the virtual word ends in the letter 'y', and if the virtual word has at least one vowel: assign the letter 'y' the /ē/ phoneme #27
10 413.

In Pass 14 of the exemplary embodiment, if the virtual word has the letter 'y', and if the letter immediately preceding the letter 'y' is the letter 'a', then: assign the letter 'y' the silence phoneme #0; assign the letter 'a' the /ā/ phoneme #26; and light the block stations for both the 'a' and the 'y' 414.

15 In Pass 15 of the exemplary embodiment, if the last letter in the virtual word is a vowel, and if there is only one vowel in the virtual word, then: if the vowel is the letter 'e', assign the letter 'e' the /ē/ phoneme #27; else if the vowel is the letter 'i', assign the letter 'i' the /ī/ phoneme #28; else if the vowel is the letter 'o', assign the letter 'o' the /ō/ phoneme #29 415.

20 In Pass 16 of the exemplary embodiment, if the virtual word has the letter 'h', and if the letter 'h' is immediately preceded by the letter 'g', and if the letter 'g' is immediately preceded by the letter 'i', then: assign the silence phoneme #0 to both the letters 'g' and 'h'; assign the /ī/ phoneme 28 to the letter 'i'; and light the block stations for the letters 'i', 'g', and 'h' 416.

30 In Pass 17 of the exemplary embodiment, if the virtual word has the letter 'o', and if the letter 'o' is immediately preceded by or immediately followed by another letter 'o', then: assign both letter 'o's the /ōō/ phoneme #43; and light the block stations for both letter 'o's 417.

In Pass 18 of the exemplary embodiment, if the virtual word has the letter 'w', and if the letter 'w' is immediately preceded by the letter 'e', then: assign both letter 'e' and letter 'w' the /ōō/ phoneme #43; and light the block stations for both letters 418.

In Pass 19 of the exemplary embodiment, if the virtual word has the letter 'u', and if the letter 'u' is immediately followed by a consonant, and if the consonant is immediately followed by the letter 'e', then: assign the letter 'e' the silence phoneme #0; assign the letter 'u' the /ōō/ phoneme #43; and light the block station for the letter 'u' and the block station for the letter 'e' 419.

In Pass 20 of the exemplary embodiment, if the virtual word has the letter 'o', and if the letter 'o' is immediately followed by the letter 'u', then: assign the letters 'o' and 'u' the /ou/ phoneme #42.; and light the block station for the letter 'o' and the block station for the letter 'u' 420.

In Pass 21 of the exemplary embodiment, if the virtual word has the letter 'g', and if the letter 'g' is immediately followed by the letter 'n', then: assign the letter 'g' the silence phoneme #0; the letter 'n' defaults to its normal sound; and light the block station for the letter 'g' and the block station for the letter 'n' 421.

In Pass 22 of the exemplary embodiment, if the virtual word has the letter 'y', and if the letter 'y' is immediately preceded by the letter 'o', then: assign the letter 'o' the /oi/ phoneme #41; assign the letter 'y' the /oi/ phoneme #41; and light the block station for the letter 'o' and the block station for the letter 'y' 422.

In Pass 23 of the exemplary embodiment, if the virtual word has the letter 'h', and if the letter 'h' is directly preceded by the letter 'w', then: assign the letter 'w' the /hw/ phoneme #24; assign the letter 'h' the /hw/ phoneme #24; and light the

block station for the letter 'w' and the block station for the letter 'h' 423.

5 In Pass 24 of the exemplary embodiment, if the virtual word has two vowels, and if the word ends in the letter 'e', and if the letter that directly precedes the letter 'e' is a consonant, then: assign the letter 'e' the silence phoneme #0; if the letter directly preceding the consonant is the letter 'a', assign the
10 letter 'a' the /ā/ phoneme #26; else if the letter directly preceding the consonant is the letter 'e', assign the letter 'e' the /ē/ phoneme #27; else if the letter directly preceding the consonant is the letter 'i', assign the letter 'i' the /ī/
15 phoneme #28; else if the letter directly preceding the consonant is the letter 'o', assign the letter 'o' the /ō/ phoneme #29; else if the letter directly preceding the consonant is the letter 'u', assign the letter 'u' the /ū/ phoneme #43; and light the block station for the letter 'e' and the block station for the vowel that directly precedes the consonant 424.

20 In Pass 25 of the exemplary embodiment, if the virtual word has two vowels, and if the word ends in the letters 'ed', and if the letter that directly precedes the letter 'e' is a consonant, then: assign the letter 'e' the silence phoneme #0; if the letter directly preceding the consonant is the letter 'a', assign the
25 letter 'a' the /ā/ phoneme #26; else if the letter directly preceding the consonant is the letter 'e', assign the letter 'e' the /ē/ phoneme #27; else if the letter directly preceding the consonant is the letter 'i', assign the letter 'i' the /ī/
30 phoneme #28; else if the letter directly preceding the consonant is the letter 'o', assign the letter 'o' the /ō/ phoneme #29; else if the letter directly preceding the consonant is the letter 'u', assign the letter 'u' the /ū/ phoneme #43; and light the block station for the letter 'e' and the block station for the vowel that directly precedes the consonant 425.

In Pass 26 of the exemplary embodiment, if the virtual word has two vowels, and if the word ends in the letters 'es', and if the letter that directly precedes the letter 'e' is a consonant, then: assign the letter 'e' the silence phoneme #0; if the letter directly preceding the consonant is the letter 'a', assign the letter 'a' the /ā/ phoneme #26; else if the letter directly preceding the consonant is the letter 'e', assign the letter 'e' the /ē/ phoneme #27; else if the letter directly preceding the consonant is the letter 'i', assign the letter 'i' the /ī/ phoneme #28; else if the letter directly preceding the consonant is the letter 'o', assign the letter 'o' the /ō/ phoneme #29; else if the letter directly preceding the consonant is the letter 'u', assign the letter 'u' the /ū/ phoneme #43; and light the block station for the letter 'e' and the block station for the vowel that directly precedes the consonant 426.

In Pass 27 of the exemplary embodiment, if the virtual word has two vowels, and if the word ends in the letters 'er', and if the letter that directly precedes the letter 'e' is a consonant, then: assign the letter 'e' the /û/ phoneme #38; if the letter directly preceding the consonant is the letter 'a', assign the letter 'a' the /ā/ phoneme #26; else if the letter directly preceding the consonant is the letter 'e', assign the letter 'e' the /ē/ phoneme #27; else if the letter directly preceding the consonant is the letter 'i', assign the letter 'i' the /ī/ phoneme #28; else if the letter directly preceding the consonant is the letter 'o', assign the letter 'o' the /ō/ phoneme #29; else if the letter directly preceding the consonant is the letter 'u', assign the letter 'u' the /ū/ phoneme #43; and light the block stations for the letters 'e' and 'r' and the block station for the vowel that directly precedes the consonant 427.

In Pass 28 of the exemplary embodiment, if the virtual word has the letter 'u', and if the letter 'u' is directly preceded by the letter 'q', then: assign the letter 'q' the /k/ phoneme

#7; assign the letter 'u' the /w/ phoneme #16; and light the block station for the letter 'q' and the block station for the letter 'u' 428.

In Pass 29 of the exemplary embodiment, if the virtual word has the letter 'p', and if the letter 'p' is directly followed by the letter 'h', then: assign the letter 'p' the /f/ phoneme #3; assign the letter 'h' the /f/ phoneme #3; and light the block station for the letter 'p' and the block station for the letter 'h' 429.

In Pass 30 of the exemplary embodiment, if the virtual word has the letter 'n', and if the letter 'n' is directly followed by the letter 'g', then: assign the letter 'n' the /ng/ phoneme #25; assign the letter 'g' the /ng/ phoneme #25; and light the block station for the letter 'n' and the block station for the letter 'g' 430.

In Pass 31 of the exemplary embodiment, if the virtual word has the letter 's', and if the letter 's' is directly followed by the letter 'h', then: assign the letter 's' the /sh/ phoneme #20; assign the letter 'h' the /sh/ phoneme #20; and light the block station for the letter 's' and the block station for the letter 'h' 431.

In Pass 32 of the exemplary embodiment, if the virtual word has the letter 't', and if the letter 't' is directly followed by the letter 'h', then: assign the letter 't' the /th/ phoneme #22; assign the letter 'h' the /th/ phoneme #22; and light the block station for the letter 't' and the block station for the letter 'h' 432.

In Pass 33 of the exemplary embodiment, if the virtual word has the letter 'a', and if the letter 'a' is directly followed by the letter 'w', then: assign the letter 'a' the /ô/ phoneme #40; assign the letter 'w' the /ô/ phoneme #40; and light the block station for the letter 'a' and the block station for the letter 'w' 433.

In Pass 34 of the exemplary embodiment, if the virtual word has the letter 'a', and if the letter 'a' is directly followed by the letter 'i', then: assign the letter 'a' the /ā/ phoneme #26; assign the letter 'i' the /ā/ phoneme #26; and light the block station for the letter 'a' and the block station for the letter 'i' 434.

In Pass 35 of the exemplary embodiment, if the virtual word has the letter 'o', and if the letter 'o' is directly followed by the letter 'a', then: assign the letter 'o' the /ō/ phoneme #29; assign the letter 'a' the /ō/ phoneme #29; and light the block station for the letter 'o' and the block station for the letter 'a' 435.

In Pass 36 of the exemplary embodiment, if the virtual word has the letter 'e', and if the letter 'e' is directly followed by the letter 'a', then: assign the letter 'e' the /ē/ phoneme #27; assign the letter 'a' the /ē/ phoneme #27; and light the block station for the letter 'e' and the block station for the letter 'a' 436.

In Pass 37 of the exemplary embodiment, if the virtual word has the letter 'd', and if the letter 'd' is directly preceded by the letter 'l', and if the letter 'l' is directly preceded by the letter 'u', and if the letter 'u' is directly preceded by the letter 'o', then: assign the letter 'o' the /ö/ phoneme #44; assign the letter 'u' the /ö/ phoneme #44; assign the letter 'l' the silence phoneme #0; assign the letter 'd' the /d/ phoneme #2; and light the block stations for the letters 'o', 'u', 'l', and 'd' 437.

In Pass 38 of the exemplary embodiment, if the virtual word has the letter 'n', and if the letter 'n' is directly preceded by the letter 'o', and if the letter 'o' is directly preceded by the letter 'i', and if the letter 'i' is directly preceded by the letter 't', then: assign the letter 't' the /sh/ phoneme #20; assign the letter 'i' the /sh/ phoneme #20; assign the letter 'o'

the /θ/ phoneme #36; assign the letter 'n' the /n/ phoneme #10;
and light the block stations for the letters 't', 'i', 'o', and
5 'n' 438.

In Pass 39 of the exemplary embodiment, if the virtual word
has the letter 'n', and if the letter 'n' is directly preceded
by the letter 'o', and if the letter 'o' is directly preceded by
the letter 'i', and if the letter 'i' is directly preceded by the
10 letter 's', then: assign the letter 's' the /sh/ phoneme #20;
assign the letter 'i' the /sh/ phoneme #20; assign the letter 'o'
the /θ/ phoneme #36; assign the letter 'n' the /n/ phoneme #10;
and light the block stations for the letters 's', 'i', 'o', and
'n' 439.

15 In Pass 40 of the exemplary embodiment, if the virtual word
has the letter 'c', and if the letter 'c' is directly preceded
by or directly followed by another letter 'c', and if the two
letter 'c's are directly followed by the letter 'e', or the
letter 'i', then: assign the first letter 'c' the /k/ phoneme #7;
20 assign the second letter 'c' the /s/ phoneme #13; and light the
block stations for the first letter 'c', the second letter 'c',
and the letter 'e' or 'i' 440.

In Pass 41 of the exemplary embodiment, if the virtual word
has the letter 'o', and if the letter 'o' is directly followed
25 by the letter 'i', then: assign the letter 'o' the /oi/ phoneme
#41; assign the letter 'i' the /oi/ phoneme #41; and light the
block station for the letter 'e' and the block station for the
letter 'i' 441.

In Pass 42 of the exemplary embodiment, if the last letter
30 of the virtual word is the letter 's', then: assign the letter
's' the /z/ phoneme #18 442.

In Pass 43 of the exemplary embodiment, if the virtual word
has the letter 'h', and if the letter 'h' is directly preceded
by the letter 'c', and if the letter 'c' is directly preceded by
35 the letter 't', then: assign the letter 't' the silence phoneme

#0; and light the block stations for the letters 't', 'c', and 'h' 443.

5 In Pass 44 of the exemplary embodiment, if the virtual word has the letter 'r' or the letter 'k', and if the letter 'h' immediately follows the letter 'r', or the letter 'k', then: assign the letter 'h' the silence phoneme #0; and light the block stations for the letter 'h', and the letter 'k' or 'r' 444.

10 In Pass 45 of the exemplary embodiment, if the virtual word has the letter 'm', and if the letter 'm' is directly followed by the letter 'b', then: assign the letter 'b' the silence phoneme #0; and light the block stations for the letters 'm', and 'b' 445.

15 In Pass 46 of the exemplary embodiment, if the virtual word has the letter 'k' or the letter 'm', and if the letter 'l' immediately precedes the letter 'k', or the letter 'm', then: assign the letter 'l' the silence phoneme #0; and light the block stations for the letter 'l', and the letter 'm' or 'k' 446.

20 In Pass 47 of the exemplary embodiment, if the virtual word has the letter 'b', and if the letter 'b' is directly followed by the letter 't', then: assign the letter 'b' the silence phoneme #0; and light the block stations for the letter 'b', and the letter 't' 447.

25 In Pass 48 of the exemplary embodiment, if the virtual word has the letter 'm', and if the letter 'm' is directly followed by the letter 'n', then: assign the letter 'n' the silence phoneme #0; and light the block stations for the letter 'm', and the letter 'n' 448.

30 In Pass 49 of the exemplary embodiment, if the last letter in the virtual word is 'h', and if the letter 'h' is directly preceded by a vowel, then; assign the letter 'h' the silence phoneme #0; and light the block stations for the letter 'h', and the vowel that precedes the letter 'h' 449.

5 In Pass 50 of the exemplary embodiment, if the first letter in the virtual word is 'w', and if the letter directly following the letter 'w' is the letter 'h', and if the letter directly following the letter 'h' is the letter 'o', then: assign the letter 'w' the silence phoneme #0; and light the block stations for the letters 'w', 'h', and 'o' 450.

10 In Pass 100 of the exemplary embodiment, if the virtual word has the letter 'd', and if the letter 'd' is directly followed by the letter 'g; or the letter 'j', then: assign the letter 'd' the silence phoneme #0; and light the block stations for the letter 'd', and the letter 'g' or 'j' 451.

15 In Pass 101 of the exemplary embodiment, if the last letter in the virtual word is 'm', and if the letter 'm' is directly preceded by the letter 's', then; assign the letter 's' the /z/ phoneme #18; and light the block stations for the letter 's' and the letter 'm' 452.

20 Exemplary code to instruct the lighting features associated with two adjacent blocks that have been identified as phonetically related (e.g., 'ch' as in the word "cheese") is depicted below:

```

25 /light2gether {
    /x1 exch def
    /x2 exch def
    /lights workingvword 2 get def
    lights x1 lights x1 get 1 x2 bitshift or put
    lights x2 lights x2 get 1 x1 bitshift or put
30 } def

```

35 Exemplary code to instruct the lighting features associated with three adjacent blocks that have been identified as phonetically related (e.g., 'ght' as in the word "light") is depicted below:

1 42624/FLC/N240

```
/light3gether {  
    /x3 exch def  
5    /x2 exch def  
    /x1 exch def  
    /lights workingvword 2 get def  
    lights x1 lights x1 get 1 x2 bitshift or put  
    lights x1 lights x1 get 1 x3 bitshift or put  
10    lights x2 lights x2 get 1 x1 bitshift or put  
    lights x2 lights x2 get 1 x3 bitshift or put  
    lights x3 lights x3 get 1 x1 bitshift or put  
    lights x3 lights x3 get 1 x2 bitshift or put  
} def
```

15 Exemplary code to instruct the lighting features associated with other blocks that have been identified as phonetically related (e.g., the silent 'e' at the end of a word with a vowel followed by a consonant, such as in the word "chase", is lighted when the player presses the 'a' block) is depicted below:

```
/lightthistoo {  
    /x2 exch def  
    /x1 exch def  
25    /lights workingvword 2 get def  
    lights x1 lights x1 get 1 x2 bitshift or put  
} def
```

30 The above lighting configuration instructions set bits in the binary template 200, the first digit of which is aligned with the player's left-most block station in which a block has been placed. Bits corresponding to the block stations to be lighted are set to "1". When all "vpasses" have been completed, the microprocessor 30 sends signals according to the lighting

35

configuration instructions to the lighting circuitry associated with each block station.

SENSING DEVICE

As mentioned above, each block station 3-7 has a floor surface 3a-7a, underneath of each of which is provided an electronic sensing device 20 as depicted in FIGS. 3a-3c, each of which is provided with its own set of analog and digital electronics as described below and as disclosed in detail in copending U.S. Utility Patent Application attorney docket number 37539/FLC/N240, the disclosure of which has previously been incorporated here by reference as if fully stated here for all purposes.

Some of the FIGURES from copending U.S. Utility Patent Application attorney docket number 37539/FLC/N240 are referred to below and are attached in Appendix C hereto. References to the FIGURES of this co-pending application and to the elements thereof are underlined to distinguish these references from the references to the FIGURES that are listed and described above.

In the exemplary embodiment of the invention depicted in, e.g. FIG. 1, each block face, e.g., 701a-701f as depicted in FIG. 10, contains on its inner surface an electrically conductive pattern that provides a unique identification of the letter depicted on the outer surface of the opposing face of the block. Exemplary identification patterns are depicted in FIGS. 20c and 21a to Appendix C and will be described below in more detail.

A. THE ELECTRONIC SENSING UNIT.

Underneath the floor surface 3a-7a of each block station 3-7 is an electronic sensing device, an exemplary embodiment of which is depicted in the schematic diagrams provided in FIGS. 2 and 3 to Appendix C. The electronic sensing device comprises a microprocessor 1, a set of drive electrodes 2-33, a series of

shift registers 35-38, and a set of at least one pickup electrode 61 configured as part of an analog circuit which is connected to
 5 an analog to digital converter 62 which communicates measured pulses to the microprocessor 1.

As depicted in FIG. 2 to Appendix C, the microprocessor 1 is connected to a set of shift registers 35-38 configured in a series. Each of the shift registers 35-38 has an input 39-42
 10 respectively and a plurality of outputs. For example, shift register 35 has outputs 43-50.

The input 39 of the first shift register 35 in the series is connected to the microprocessor 1. Each shift register output, e.g., 43-50, is connected to one of the drive electrodes, e.g., 2-9. The microprocessor 1 is programmed to digitally
 15 generate drive signals to each of said drive electrodes 2-33 through the shift registers 35-38.

During the time that the base sensing unit is turned on, the microprocessor 1, as depicted in FIG. 2 to Appendix C, repeatedly
 20 initiates consecutive sensing cycles. Each sensing cycle consists of the microprocessor 1 consecutively stimulating, or "firing", drive electrodes 2 through 33. Simultaneous with the firing of each drive electrode, the microprocessor 1 is programmed to wait for specified amount of time, referred to
 25 herein as the "response time." At the expiration of the response time, the microprocessor 1 instructs the analog to digital converter 62 to measure a pulse received from the analog pickup electrode circuitry depicted in FIG. 3 to Appendix C.

The response time is the amount of time that it takes for
 30 the particular circuitry to conduct an impulse picked up by the pickup electrode 61, and send the impulse through the operational amplifiers 63-65 to the analog to digital converter 62. The response time is measured, such as through laboratory testing of the circuitry or by sending a test impulse through the analog
 35 circuitry. A test impulse of a certain magnitude can be sent

when the base unit 1 as depicted in FIG. 1 is first turned on from the microprocessor 1 to the pickup electrode 61. In the case of the test impulse, the microprocessor 1 instructs the analog to digital converter 62 to communicate each changed impulse received until the microprocessor 1 receives an impulse equal to the magnitude of the test impulse. The microprocessor 1 measures the elapsed time between the time that the test impulse is sent and the time that an impulse is received with the magnitude equal to the test impulse.

During the time that the base sensing unit is turned on, the microprocessor 1 repeatedly initiates a new sensing cycle as soon as it has completed the previous sensing cycle.

As depicted in FIG. 3 to Appendix C, the pickup electrode 61 is part of an analog circuit. The pickup electrode is connected to a set of operational amplifiers 63-65, (sometimes referred to as "op amps") for amplifying induced charge pulses picked up by the pickup electrode 61. In one embodiment, operational amplifier model LM324 is used, as depicted in FIG. 3 to Appendix C. As depicted in FIG. 6 to Appendix C, the pickup electrode 61 is configured in the central area of a circular planar array of drive electrodes.

The analog circuit has a plurality of outputs through a connection 67 to the analog digital converter 62. The analog digital converter 62 in the embodiment depicted in FIG. 2 to Appendix C is part of the microprocessor 1. The analog to digital converter 62 feeds the measured pulses to microprocessor 1. In other embodiments, the analog to digital converter is separate from the microprocessor 1 as is depicted and as will be discussed below in connection with FIG. 12 to Appendix C.

An output of the analog circuit is a pair of pulses, one going positive; the other going negative. Each pulse is measured by the analog digital converter 62. The height difference between the pulses is used to determine whether the response is

a "0" or a "1". The timing of these pulses in relationship to the shifting of the stimulus drive signal is used by the microprocessor 1 to determine the identification code of a block in a block station 3-7.

The microprocessor 1 is programmed to recognize as a "1" a certain range of voltage. The identification of a range is dependent upon the particular hardware component selected to act as the microprocessor 1. It is useful, but not a limitation of the invention, to set the range of voltage to be recognized as a "1" to be greater than or equal to half the amount that is the total of the maximum voltage expected for a "1" and the minimum voltage expected for a "0".

A general expression of the number of measurements taken is that there are "N" drive electrodes, "N" corresponding pattern pieces in the identifying pattern, and "N" measurements made for each sensing cycle, resulting in an "N" bit binary value for each cycle. Encoding of an identification of a particular object is discussed below.

The microprocessor 1 deduces the distance between a block and the sensing array of drive and pickup electrodes for the particular block station 3-7 in which the block rests by calculating the difference between the pulse height, or pulse magnitude, measured by the pickup electrode 61 as compared to a table of calibrated impulse measurements. As was explained above, determination of the distance information is used to place the base unit 1 of the toy in different modes of operation.

FIGS. 4a and 4b to Appendix C are semi-schematic diagrams of a partial view of a single drive electrode, e.g., 2, as embodied in a circular planar array 200 of drive electrodes as shown in FIG. 6 to Appendix C. FIG. 4a to Appendix C is a top view of a single drive electrode 2; FIG. 4b to Appendix C is the underneath view of drive electrode 2; FIG. 6 to Appendix C is a schematic diagram depicting the underneath side of an exemplary

embodiment of a circuit board comprising the hardware components of the base sensing device aspect of the invention. As depicted in FIG. 4a to Appendix C, the top surface of drive electrode 2 comprises a pie-shaped wedge of electrically conductive material 2-1. A four-sided embodiment is depicted in FIG. 21a to Appendix C.

A cylinder of electrically conductive material 2-2 pierces through from the top electrically conductive surface 2-1 of drive electrode 2 through to a surface of nonconductive material, such as a shielding ground layer 85, underneath the electrically conductive layer 2-1 of drive electrode 2 as depicted in FIG. 4b to Appendix C. It should be noted that the detailed view of the underneath surface of the shielding ground layer 85 as depicted in FIG. 4b to Appendix C is not an indication of any particular shape of the shielding ground layer 85.

The top end 2-2a of the electrically conductive cylinder contacts the pie-shaped wedge of electrically conductive material 2-1. As is depicted in FIG. 4b, the underneath end 2-2b of the electrically conductive cylinder is exposed for a connection 43, in this configuration, to a shift register 35 as depicted in FIG. 2 to Appendix C. General references herein to a drive electrode use the unqualified reference numeral, e.g., 2 which includes the electrically conductive cylinder, e.g., 2-2 (and the cylinder's top end 2-2a and the cylinder's bottom end 2-2b) as well as the electrically conductive surface material such as the pie-shaped wedge, e.g., 2-1, depicted in FIG. 4a to Appendix C.

The microprocessor 1 fires a drive signal to shift register 35 which is sent to drive electrode 2 through connection 43. The drive signal is conducted from the underneath end 2-2b to the top end 2-2a of the electrically conductive cylinder to the top surface 2-1 of the electrode 2. The drive electrodes 2-33 in the sensing device as previously discussed are configured in an array, an exemplary configuration of which is a circular planar

array 200 on the surface of a circuit board as depicted in FIG. 6 to Appendix C. Those with ordinary skill in the art will understand that other embodiments of the invention use other configurations of the drive electrodes without departing from the spirit of the invention.

In the same plane with the drive electrodes 2-33, one or more pickup electrodes are configured. In the embodiment of the invention depicted in FIG. 6 to Appendix C, a single pickup electrode 61 is configured in the same plane of the planar array 200 of pickup electrodes 2-33. In the four-sided configuration depicted in FIGS. 20a, 20c and 21a to Appendix C, only 12 electrodes 2-13 are provided.

As depicted in a detail view of electrode 2 in FIG. 11 to Appendix C, an exemplary embodiment provides that each drive electrode is isolated from each other drive electrode and from the pickup electrode 61, by a combination of electrically nonconductive material, e.g., 202-2 and 207, and electrically conductive material 201-2. That is, the isolation bands comprise electrically conductive material 201-2 in between electrically nonconductive material, e.g., 202-2 and 207. The electrically conductive material in the isolation band is grounded, e.g., 201-1 is connected to the ground circuitry 70 depicted in FIG. 3 to Appendix C. This type of isolation band combination is depicted in further detail in a four-sided planar embodiment of the sensing device depicted in FIG. 21a to Appendix C. Throughout the description of this invention, reference to elements of figures with a cross-hatch pattern or darkened shading indicates that the material referenced is electrically conductive material.

B. THE OBJECT TO BE SENSED.

Turning to the configuration of the object to be identified, in the exemplary embodiment described herein, the object is a block 701 with six faces 701a-701f as depicted in FIG. 10.

Inside each of the six faces 701a-701f is an identifying pattern made of electrically conductive material such as the exemplary identifying pattern depicted in FIG. 20c to Appendix C. In the exemplary embodiment described here, the identifying pattern inside the surface of a face of a block identifies the letter represented on the opposing face of the block. For example, as depicted in FIG. 10, an identifying pattern inside the surface of block face 701e identifies as the letter "A" the letter exposed on the outside surface of block face 701a.

The identifying pattern can be, among other things, for example, a simple single-sided printed circuit board or a pattern printed with conductive ink on the inside of the object base's bottom surface. As depicted in FIG. 20c to Appendix C, there is a central transmitting area 119-1. The identifying pattern is further comprised of a plurality of pickup area pattern pieces 107-1 - 118-1. When the block 701 is placed in a receiving block station 3-7, the central transmitting area 119-1 aligns over analog pickup electrode 61-2-1 as depicted in FIG. 21a to Appendix C.

In the embodiment described herein, the number of pickup pattern pieces in the identifying pattern is equal to the number of drive electrodes in the sensing device base unit 1. It should be noted that in alternative embodiments of the present invention, the number of drive electrodes is a multiple of the number of pickup pattern pieces in the identifying pattern.

As shown in the exemplary identification pattern depicted in FIG. 20c to Appendix C, the identification pattern provides a plurality of electrically conducting areas (109-1, 114-1, and 116-1). As is explained in further detail below, the sensing device identifies the block 701 by identifying which of the pickup pattern pieces 107-1 - 118-1 are aligned over each of the twelve (12) drive electrodes in the case of the four-sided embodiment depicted in FIGS. 20a, 20c, and 21a to Appendix C.

The pattern of conductive and nonconductive areas of the object identification pattern layer corresponds to a unique bit pattern.

5 The microprocessor 1 rotates through the identifying pattern bit by bit until it identifies the bit pattern key. In such an embodiment, it is necessary to select the proper values for "N" (the number of drive electrodes which is also equal to the number of pickup area pattern pieces in the identifying pattern) and "K" 10 (the number of connections between the pickup areas and the common transmitting area 119) so that there is a unique pattern for each object in the object set to be sensed such that none of the patterns selected can be misidentified as one of the other patterns in the object set as the microprocessor 1 rotates 15 through the identifying pattern. The patterns so selected are referred to herein as "non-conflicting" keys, or patterns.

In selecting the values for "N" and "K" for an embodiment that does not use a start of key bit pattern, certain rules are useful in developing the appropriate keys: 1) each pattern must 20 be unique with respect to all other patterns for all possible rotations of the object 104 in the block station 102; 2) No key/pattern contains consecutive "1's" - that is, there must be at least one "0" between each "1"; and 3) there must be the same number of "1's" in each pattern so that the capacitance of the 25 sensing plate is the same for all objects.

C. CAPACITIVE COUPLING.

FIG. 11 to Appendix C depicts an electrically conductive identifying pattern in the base 105 of an object 104 in close 30 essentially horizontal proximity to a sensing drive electrode/pickup electrode array located under the floor surface 103 (3a-7a) of a block station 102 (3-7) of the base unit 1. The depicted orientation is properly aligned to allow capacitive coupling in that a particular drive electrode, e.g., 2, when 35 fired with a drive signal will capacitively induce a charge in

the pickup area 107 of the electrically conductive material in the identification pattern contained in the base 105 of object 104 such that the electrically conductive identifying pattern will conduct the induced charge to the common transmitting area 119 which will in turn induce a charge in the pickup electrode 61 (depicted as two sub-components 61-1 and 61-2).

FIG. 12 to Appendix C depicts another view of the object 104 to be identified with the base 105 in close essentially horizontal proximity to the sensing device feature of the present invention. FIG. 12 to Appendix C depicts the path of a charge resulting in the capacitive coupling of the sensing device with the object 104 to be identified.

As depicted in FIG. 12 to Appendix C, the microprocessor 1 generates a drive signal to a drive electrode, e.g., 2. The drive signal is transmitted from the microprocessor 1 through the input 39 to the shift register 35 and then through the output 43 of the shift register 35 to the drive electrode 2. If a conductive pickup area, e.g., 107, is aligned over the drive electrode 2, then the drive electrode 2 will induce a charge 81 over the gap between the drive electrode 2 and the conductive pickup area 2.

It should be noted that the term "aligned" as used herein does not require exact and complete alignment of the entire pickup area of the identifying pattern over the entire surface area of the electrode. Partial alignment is sufficient to allow the inducement of a charge from the drive electrode to a pickup area. The "range" recognized as a "1" as previously described above accounts for partial and full alignment.

The charge induced in the pickup area 107 is then transmitted 82 to the common transmitting area 119. The common transmitting area 119 will in turn induce a charge 83 over the gap between the common transmitting area 119 and the analog pickup electrode 61 in the block station well. The analog pickup

electrode 61 will transmit the picked up pulse to the analog digital converter 62.

5 As depicted in FIG. 12 to Appendix C, each time that the microprocessor 1 sends a drive signal to one of the drive electrodes, e.g., 2, the microprocessor 1 instructs 66 the analog to digital converter 62 as depicted in FIG. 12 to Appendix C, to measure a pulse. As each drive electrode is fired with a drive
10 signal from the microprocessor 1, if the drive electrode, e.g., 2, is aligned under a conductive pickup area, e.g., 107, of an object 104, then the portion of the pickup area and the common transmitting area 119 of the electrically conductive identifying pattern becomes capacitively coupled with the drive
15 electrode/pickup electrode planar array.

The phrases "capacitively coupled" and "capacitive coupling" mean the inducement of a charge by a drive electrode to a receiving conductive area, either over a gap of free space or through one or more layers of electrically nonconductive
20 dielectric material, such that the charge is then conducted to a transmitting area that subsequently induces a charge to a pickup electrode, over a different area of the same gap of free space or one or more layers of electrically nonconductive dielectric material.

25 As depicted in FIG. 12 to Appendix C, the pickup electrode 61 picks up a pulse from the top surface of the pickup electrode 61-2 and 61-1a, and conducts the charge to the underneath end of the electrically conductive cylinder 61-1b which is connected 69 to a set of operational amplifiers 63-65 which are in turn
30 connected 67 to an analog to digital converter 62 which is connected to communicate 68 or otherwise communicates 68 the measured pulse with the microprocessor 1.

Because, as was previously described above, the microprocessor 1 instructs the analog to digital converter 62 to
35 measure an incoming pulse at a certain time after the

microprocessor 1 sends a drive signal to a drive electrode, e.g., 2, the analog to digital converter 62 will in turn measure the pulse and communicate the pulse in digital form to the microprocessor 1. In some embodiments of the present invention, the analog to digital converter 62 is part of, and included in, the microprocessor 1. Such is the case in the embodiment depicted, for instance, in FIG. 2 to Appendix C.

As depicted in FIG. 12 to Appendix C, the embodiments of the invention described herein sandwich the drive electrodes, e.g., 2, between a shielding ground plane layer 85 and a surface layer of dielectric material 84. As is also depicted in FIG. 12 to Appendix C, the embodiments of the invention described herein provide the identifying pattern, e.g., pickup area 107 and common transmitting area 119, as a layer of electrically conductive material inside the bottom surface of the base 105 of the object 104. It should be understood by one of ordinary skill in the art that in alternative embodiments, capacitive coupling is provided if either or both the drive electrode/pickup electrode array and the identifying electrically conductive pattern are exposed to air, liquid, gel, or other materials.

The microprocessor 1 knows the location of each drive electrode 2-33, or in the case of the four-sided embodiment depicted in FIGS. 20a, 20c, and 21a to Appendix C electrodes 2-13, and generates a drive signal to each of the drive electrodes in serial fashion over a complete sensing cycle.

Once the microprocessor 1 has assembled a raw bit pattern, the microprocessor interprets the bit pattern as a key into a lookup table 87 as shown in FIG. 12 to Appendix C. In the exemplary embodiment described herein, the object 104 is a block with a letter. The microprocessor 1 interprets the bit pattern and then locates the identifier of the object 104 in the lookup table 87.

As depicted in FIG. 12 to Appendix C, the microprocessor 1 provides the digital sound representation identifier to audio circuitry 88 for delivery to speakers 89 contained in the exemplary toy embodiment. FIG. 18 depicts an exemplary embodiment of such audio circuitry.

D. ANALYZING THE IDENTIFYING PATTERN.

As disclosed in U.S. Provisional Patent Application Serial No. 60/165985, the disclosure of which has previously been incorporated here by reference as if fully stated here for all purposes, the microprocessor 1 is programmed to measure each induced charge picked up by the pickup electrode 61 and to assemble a set of the measured charges into a bit pattern for each sensing cycle. The magnitude of the signal at the output of the analog circuitry in response to the stimulus signal is proportional to the area of the stimulus electrode, the area of the pickup electrode, and the spacing between them. While an object, e.g., 104, with a base e.g., 105, containing an identifying pattern, e.g. as depicted in FIG. 20c to Appendix C, is resting in floor 3a-7a of a block station 3-7, as the microprocessor 1 shifts the stimulus around the array of electrodes 2-33, the pickup electrode 61 picks up pulses and communicates the pulses through a set of operational amplifiers 63-65 to the analog to digital converter 62 for communication to the microprocessor 1.

Once the microprocessor 1 has assembled a raw bit pattern, the microprocessor 1 interprets the bit pattern as a key into a lookup table 87 as shown in FIG. 12 to Appendix C.

ILLUSTRATIVE EMBODIMENTS

Although this invention has been described in certain specific embodiments, many additional modifications and

variations would be apparent to those skilled in the art. It is,
therefore, to be understood that this invention may be practiced
5 otherwise than as specifically described. Thus, the embodiments
of the invention described herein should be considered in all
respects as illustrative and not restrictive, the scope of the
invention to be determined by the appended claims and their
equivalents rather than the foregoing description.

10

15
20
25

30

35